

BRACHE TONDE A TRATTI MULTIPLI, EN1492-2 / Round Slings Multi Legs, EN1492-2

Le brache tonde a tratti multipli sono realizzate con:

- Brache tonde asolate in poliestere.
- Accessori in acciaio in grado 80 o 100.

La connessione tra gli elementi in poliestere e quelli in acciaio avviene attraverso le sagole. Rappresentano una valida alternativa alle brache in catena: sono leggere, flessibili, non graffiano la superficie del carico, non arrugginiscono. Sono particolarmente indicate dove la braca non deve condurre elettricità.

Caratteristiche tecniche

- Portata (WLL) fino a 63 ton.
- Coeff. di sicurezza 4:1 (accessori acciaio).
- Coeff. di sicurezza 7:1 (brache poliestere).
- Lunghezza MIN= 0,5 m.
- Lunghezza MAX= 20 m.
- Conformi a DM2006/42/CE, EN1492-2.

Multi leg round slings are made of:

- Polyester eye-eye round slings.
- Grade 80 or 100 steel components.

Connection between polyester slings and metal parts is by special webbing connectors. They represent a valid alternative to chain slings: they are light, flexible, do not scratch the load surface, do not rust. They are particularly indicated where the slings don't have to conduct electricity.


Technical features

- WLL up to 63 ton.
- Safety factor 4:1 (steel components).
- Safety factor 7:1 (polyester slings).
- MIN Length= 0,5 m.
- MAX Length= 20 m.
- Conform to DM2006/42/CE, EN1492-2.


BRACHE AD 1 TRATTO / 1 Legs Sling			
Colour	Code	WLL (ton)	
		90°	
Violet	R1-010	1	
Green	R1-020	2	
Yellow	R1-030	3	
Grey	R1-040	4	
Red	R1-050	5	
Brown	R1-060	6	
Blue	R1-080	8	
Orange	R1-100	10	
Orange	R1-150	15	
Orange	R1-200	20	
Orange	R1-250	25	
Orange	R1-300	30	




BRACHE A 2 TRATTI / 2 Legs Sling			
Colour	Code	WLL (ton)	
		7°<β<45°	45°<β<60°
Violet	R2-014	1,4	1
Green	R2-028	2,8	2
Yellow	R2-042	4,2	3
Grey	R2-056	5,6	4
Red	R2-070	7	5
Brown	R2-084	8,4	6
Blue	R2-112	11,2	8
Orange	R2-140	14	10
Orange	R2-210	21	15
Orange	R2-280	28	20
Orange	R2-350	35	25
Orange	R2-420	42	30



BRACHE A 3 TRATTI / 3 Legs Sling			
Colour	Code	WLL (ton)	
		7°<β<45°	45°<β<60°
Violet	R3-210	2,1	1,5
Green	R3-420	4,2	3
Yellow	R3-630	6,3	4,5
Grey	R3-840	8,4	6
Red	R3-105	10,5	7,5
Brown	R3-126	12,6	9
Blue	R3-168	16,8	12
Orange	R3-210	21	15
Orange	R3-315	31,5	22,5
Orange	R3-420	42	30
Orange	R3-525	52,5	37,5
Orange	R3-630	63	45



BRACHE A 4 TRATTI / 4 Legs Sling			
Colour	Code	WLL (ton)	
		7°<β<45°	45°<β<60°
Violet	R4-210	2,1	1,5
Green	R4-420	4,2	3
Yellow	R4-630	6,3	4,5
Grey	R4-840	8,4	6
Red	R4-105	10,5	7,5
Brown	R4-126	12,6	9
Blue	R4-168	16,8	12
Orange	R4-210	21	15
Orange	R4-315	31,5	22,5
Orange	R4-420	42	30
Orange	R4-525	52,5	37,5
Orange	R4-630	63	45



COMPONENTI AGGIUNTIVI - ADDITIONAL COMPONENTS

